


# TrueSafe Comfort<sup>®</sup> BC



## Push Button Style Safety IV Catheter

Blood Control with Active Check Valve Technology

With VenaPUR<sup>®</sup>



### SPECIFICATIONS



- Incorporated blood control
- VenaPUR<sup>®</sup> catheter material
- Push button style needle retraction
- Ground stainless-steel needle
- Straight hub
- Disposable
- Not made with natural rubber latex
- Not made with DEHP
- Non-pyrogenic
- ISO compliant color coding
- Needlestick Safety and Prevention Act (NSPA) of 2000 compliant



www.medsourcelabs.com

Item #	Gauge and Length	Catheter ID (mm)	Catheter OD (mm)	Gravity Flow Rate (mL/min)	UOM
MS-86414	14G x 1.75"	1.6mm	2.1mm	297mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS
MS-86416	16G x 1.77"	1.38mm	1.8mm	220mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS
MS-864162	16G x 1.16"	1.38mm	1.8mm	220mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS
MS-864182	18G x 1.88"	0.95mm	1.3mm	94mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS
MS-86418	18G x 1.16"	0.95mm	1.3mm	94mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS
MS-864202	20G x 1.88"	0.78mm	1.1mm	61mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS
MS-86420	20G x 1.16"	0.78mm	1.1mm	61mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS
MS-864203	20G x 1.00"	0.78mm	1.1mm	61mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS
MS-86422	22G x 1.00"	0.62mm	0.9mm	36mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS
MS-86424	24G x 0.75"	0.49mm	0.7mm	20mL/min	50 EA/BX, 4 BX/CS, 200 EA/CS